

ASH

A: Typical structural appearance of rift and plain cut, virtually knotless, occasional knot points possible, no brown heart, slight colour variations possible, jointfree gluing.

B: Typical structural appearance of rift and plain cut; sound knots possible, occasional dead knots, knotholes professionally filled, brown heart possible, natural colour variations, jointfree gluing.



The above picture shows an example of the natural character of the wood, this will vary in every panel. Variations in colour and grain patterns are natural and inevitable. A picture is never a substitute for the "real thing". For this reason we recommend a visit to your nearest Admonter dealer. He will be pleased to show you samples.

STIA Norm	Thickness mm app.	Length mm (Width 2030)	Top layer thickness mm	Top layer width mm	Middle layer	Packaging pack./palett
A/B	12	2000/2100/2400	3,6	93/114 only 2100/2400 mm	BML softwood	25
A/B	19	2000/2100/2400	3,6		SML softwood	30
A/B	19	2400	3,6		Plywood	30
A/B	19	2000/2100/2400	3,6	158 only in lengths 2000 and 2400 mm available!	Ash	30
A/B	29	2000/2100/2400	3,6		SML softwood	20
A/B	29	2400	3,6		Plywood	20
A/A	40	2400	3,6		Spruce 5-layer	10

SWP/3 non structural (ns): Solid wood panels for non-structural use in wet areas.

Legend: SML = strip core, BML = board middle layer.