

ASH MEDIUM

A: Typical structural appearance of rift and plain cut, virtually knotless, knot points possible, thermo treatment, natural colour variations and colour streaks possible, jointfree gluing.

B: Typical structural appearance of rift and plain cut; sound knots and dead knots possible, knotholes and shakes professionally filled, occasional brown heart possible, thermo treatment, natural colour variations and occasional colour streaks possible, jointfree gluing.



The above picture shows an example of the natural character of the wood, this will vary in every panel. Variations in colour and grain patterns are natural and inevitable. A picture is never a substitute for the "real thing". For this reason we recommend a visit to your nearest Admonter dealer. He will be pleased to show you samples.

STIA Norm	Thickness mm app.	Length mm (Width 2030)	Top layer thickness mm	Top layer width mm	Middle layer	Packaging pack./palett
A/B	12	2000	3,6	158	BML softwood	25
A/B	19	2000	3,6	158	SML softwood	30
A/B	19	2400	3,6	158	Plywood	30
A/B	29	2000	3,6	158	SML softwood	20
A/B	29	2400	3,6	158	Plywood	20
A/A	40	2400	3,6	158	Spruce 5-layer	10

SWP/3 non structural (ns): Solid wood panels for non-structural use in wet areas.

Legend: SML = strip core, BML = board middle layer.