

# ROBINIA DARK

**B:** Typical structural appearance of rift and plain cut, surface full of natural character, knotholes and shakes professionally filled, thermo treatment, natural colour variations enhanced by the thermo-treatment are a valued feature, jointfree gluing.



Characteristics

The above picture shows an example of the natural character of the wood, this will vary in every panel. Variations in colour and grain patterns are natural and inevitable. A picture is never a substitute for the "real thing". For this reason we recommend a visit to your nearest Admonter dealer. He will be pleased to show you samples.

STIA Norm	Thickness mm app.	Length mm (Width 2030)	Top layer thickness mm	Top layer width mm	Middle layer	Packaging pack./palett
B/B	12	2100 (Top-l. width 93)/ 2400 (Top-l. width 158)	3,6	93/158	BML softwood	25
B/B	19	2100 (Top-l. width 93)/ 2400 (Top-l. width 158)	3,6	93/158	SML softwood	30
B/B	19	2400	3,6	158	Plywood	30
B/B	29	2100 (Top-l. width 93)/ 2400 (Top-l. width 158)	3,6	93/158	SML softwood	20
B/B	29	2400	3,6	158	Plywood	20
B/B	40	2100 (Top-l. width 93)/ 2400 (Top-l. width 158)	3,6	93/158	Spruce 5-layer	10

**SWP/3 non structural (ns):** Solid wood panels for non-structural use in wet areas.

**Legend:** SML = strip core, BML = board middle layer.

