


AMERICAN WALNUT 2BOND TWIN - HERRINGBONE



Initial care - with Admonter maintenance oil

You can find more information in the Admonter care- and laying instructions and at www.admonter.eu/en/downloads/



Admonter Natural Floor on under-floor-heating-system

Admonter Natural Floors are ideally suited for under-floor heating systems. We recommend hot-water underfloor heating systems set at low temperature. The surface temperature of 29°C must not be exceeded.

The only exception is Beech. We suggest that our products ideally are fully glued down for best results with Admonter elastic adhesive. However, like all engineered boards our planks can be laid as a floating installation (except 2-layer floors and 3-layer floors small (SF-RS), they have to be fully glued down).

More information at www.admonter.at or contact your specialist dealer.

Skirting: Typ1, Typ3 b, Typ4

Grading	Thickn. mm	Width mm	Length mm	Installation and construction			Surface	Texture
				Tongue & groove	lock-it			
elegance	10	120	590	2-layer	-	-	natural oil	sanded

Admonter flooring is a 100 % natural product. A picture is never a substitute for the „real thing“. For this reason we recommend a visit to your nearest Admonter flooring dealer. He will be pleased to show you samples.

Technical information							
Wood species	Thickness mm	Weight (kg/m ²)	Moisture content (%)	Lambda	d-Value	Hardness	Fire classification
Am. Walnut 2bond twin - Herringbone	10	5,5	7+/-2	0,16	0,063	36	C _{fl} -s1

LH-RS: Hardwood-backing / **NH-RS:** Softwood-backing
SF-RS: Softwood-veneer-backing, **ng:** natural oiled / **uv:** UV oiled / **ml:** matt lacquer

For more information visit our website www.admonter.at

February 2015

