

Oak Sesto

Top layer
approx. 3,6 mm
thermo-treated



FLOORs



Admonter FLOORs on underfloor heating systems

Admonter FLOORs are ideally suited for underfloor heating systems. We suggest that our products ideally are fully glued down for best results with Admonter elastic adhesive. However, like all engineered boards our planks can be laid as a floating installation (except 2-layer floors and 3-layer floors small, they have to be fully glued down). We recommend hot-water underfloor heating systems set at low temperature. Please find detailed information in the information sheet *Admonter FLOORs on underfloor heating systems!*

Admonter accessories

The wide range of accessories matches the Admonter FLOORs and includes flush-mount skirting and solutions for staircases.

Regular care and maintenance

Please see the Admonter maintenance & installation instructions GB 2017.

Further information

<http://www.admonter.eu/en/downloads/>

Grading	Thickn. mm	Width mm	Length mm <i>subject to availability</i>		Installation and construction		Finish	Texture
					Tongue & groove	lock-it		
rustic	15	188	classic	1850/2000/2400	3-layer	-	ng	brushed

ng: natural oiled easy care / uv: UV oiled / ml: matt lacquer

Please note: natural oiled easy care: no FINAL COAT OF OIL required after installation! Repair and supplementary oil please find in our price list.

Technical information

More information (for example concerning fire classification) in the accompanying information to CE-marking at <http://www.admonter.eu/en/downloads/>

Type of wood	Thickness (mm)	Weight [kg/m ²]	Moisture content [%]	Lambda [W/m K]	d-Value R [m ² K/W]	Hardness [N/mm ²]	Fire classification
Oak medium	15	7,7	5+/-2	0,14	0,107	41	C _f -s1



More information at www.admonter.at