


# LARCH Nata

Top layer  
approx. 3,6 mm 

FLOORs



### Admonter FLOORs on underfloor heating systems

Admonter FLOORs are ideally suited for underfloor heating systems. We suggest that our products ideally are fully glued down for best results with Admonter elastic adhesive. However, like all engineered boards our planks can be laid as a floating installation (except 2-layer floors and 3-layer floors small, they have to be fully glued down). We recommend hot-water underfloor heating systems set at low temperature. Please find detailed information in the information sheet *Admonter FLOORs on underfloor heating systems!*

### Admonter accessories

The wide range of accessories matches the Admonter FLOORs and includes flush-mount skirting and solutions for staircases.

### Regular care and maintenance

Please see the Admonter maintenance & installation instructions GB 2017.

### Further information

<http://www.admonter.eu/en/downloads/>

Grading	Thickn. mm	Width mm	Length mm <i>subject to availability</i>		Installation / construction		Finish	Texture
					t&g	lock-it		
rustic	15	161	classic	1850/2000/2400	3-layer	-	ng	cross
	15	195	classic	1850/2000/2400	3-layer	-	ng	cross

ng: natural oiled easy care / uv: uv oiled / ml: matt lacquer

**Please note:** natural oiled easy care: no FINAL COAT OF OIL required after installation! Repair and supplementary oil please find in our price list.

### Technical information

More information (for example concerning fire classification) in the accompanying information to CE-marking at <http://www.admonter.eu/de/downloads/>

Wood species	Thickn. (mm)	Weight [kg/m <sup>2</sup> ]	Moisture content [%]	Lambda [W/m K]	d-Value R [m <sup>2</sup> K/W]	Hardness [N/mm <sup>2</sup> ]	Fire classification
Larch	15	7,8	8+/-2	0,14	0,107	20	C <sub>fl</sub> -s1



More information at [www.admonter.at](http://www.admonter.at)