

OAK 2BOND TWIN - HERRINGBONE

FLOOR S



Initial care - with Admonter maintenance oil

You can find more information in the Admonter care- and laying instructions and at www.admonter.eu/en/downloads/



Admonter Natural Floor on under-floor-heating-system

Admonter Natural Floors are ideally suited for under-floor heating systems. We recommend hot-water underfloor heating systems set at low temperature. The surface temperature of 29°C must not be exceeded.

The only exception is Beech. We suggest that our products ideally are fully glued down for best results with Admonter elastic adhesive. However, like all engineered boards our planks can be laid as a floating installation (except 2-layer floors and 3-layer floors small (SF-RS), they have to be fully glued down).

More information at www.admonter.at or contact your specialist dealer.

Skirting: Typ1, Typ3, Typ3 b, Typ4

Grading	Thickn. mm	Width mm	Length mm	Installation and construction			Surface	Texture
				Tongue & groove	lock-it			
elegance	10	120	590	2-layer	-	-	natural oil	brushed

Technical information

Wood species	Thickness mm	Weight (kg/m ²)	Moisture content (%)	Lambda	d-Value	Hardness	Fire classification
Oak 2bond twin - Herringbone	10	6,0	7+/-2	0,15	0,067	41	C _{fl} -s1

LH-RS: Hardwood-backing / NH-RS: Softwood-backing
SF-RS: Softwood-veneer-backing, ng: natural oiled / uv: UV oiled / ml: matt lacquer



For more information visit our website www.admonter.at

February 2015

A brand of STIA Holzindustrie GmbH, Sägestrasse 539, 8911 Admont, Austria
Errors and changes possible, phone: +43(0)3613/3350-0, fax: +43(0)3613/3350-119, info@admonter.at, www.admonter.at