

OAK IGNIS



Initial care - with Admonter maintenance oil

You can find more information in the Admonter care- and laying instructions and at www.admonter.eu/en/downloads/



Admonter Natural Floor on under-floor-heating-system

Admonter Natural Floors are ideally suited for under-floor heating systems. We recommend hot-water underfloor heating systems set at low temperature. The surface temperature of 29°C must not be exceeded.

The only exception is Beech. We suggest that our products ideally are fully glued down for best results with Admonter elastic adhesive. However, like all engineered boards our planks can be laid as a floating installation (except 2-layer floors and 3-layer floors small (SF-RS), they have to be fully glued down).

More information at www.admonter.at or contact your specialist dealer.

Skirting: Typ2, Typ3, Typ3 white, Typ4

Grading	Thickn. mm	Width mm	Length mm	Installation and construction			Surface	Texture
				Tongue & groove		lock-it		
basic	15	192	1850/2000/2400	-	3-layer ^{NH-RS}	3-layer ^{NH-RS}	natural oil	brushed, cross, alpin
	15	192	4000/4500/5000	3-layer ^{LH-RS}	-	-	natural oil	brushed, cross, alpin
	15	240	4000/4500/5000	3-layer ^{LH-RS}	-	-	natural oil	brushed, cross, alpin
	15	280	4000/4500/5000	3-layer ^{LH-RS}	-	-	natural oil	brushed, cross, alpin
	15	325	4000/4500/5000	3-layer ^{LH-RS}	-	-	natural oil	brushed, cross, alpin
rustic	10	158	1850/2000	-	-	2-layer	natural oil	brushed
	10	192	1850/2000	-	-	2-layer	natural oil	brushed
	15	192	1850/2000/2400	-	3-layer ^{NH-RS}	3-layer ^{NH-RS}	natural oil	brushed, cross, alpin
	15	192	4000/4500/5000	3-layer ^{LH-RS}	-	-	natural oil	brushed, cross, alpin
	15	240	4000/4500/5000	3-layer ^{LH-RS}	-	-	natural oil	brushed, cross, alpin
	15	280	4000/4500/5000	3-layer ^{LH-RS}	-	-	natural oil	brushed, cross, alpin
	15	325	4000/4500/5000	3-layer ^{LH-RS}	-	-	natural oil	brushed, cross, alpin

Technical Information

Wood species	Thickness mm	Weight (kg/m ²)	Moisture content (%)	Lambda	d-Value	Hardness	Fire classification
Oak	10	6,4	7+/-2	0,15	0,073	41	C _{fl} -s1
Oak	15	8,5	7+/-2	0,14	0,107	41	C _{fl} -s1

LH-RS: Hardwood-backing / **NH-RS:** Softwood-backing
SF-RS: Softwood-veneer-backing, **ng:** natural oiled / **uv:** UV oiled / **ml:** matt lacquer

For more information visit our website www.admonter.at

February 2015

