

# OAK SUPERBIANCO



### Initial care - with Admonter maintenance oil

You can find more information in the Admonter care- and laying instructions and at [www.admonter.eu/en/downloads/](http://www.admonter.eu/en/downloads/)



### Admonter Natural Floor on under-floor-heating-system

Admonter Natural Floors are ideally suited for under-floor heating systems. We recommend hot-water underfloor heating systems set at low temperature. The surface temperature of 29°C must not be exceeded.

The only exception is Beech. We suggest that our products ideally are fully glued down for best results with Admonter elastic adhesive. However, like all engineered boards our planks can be laid as a floating installation (except 2-layer floors and 3-layer floors small (SF-RS), they have to be fully glued down).

More information at [www.admonter.at](http://www.admonter.at) or contact your specialist dealer.

**Skirting:** Typ1, Typ3 white, Typ4

Grading	Thickn. mm	Width mm	Length mm	Installation and construction			Surface	Texture
				Tongue & groove		lock-it		
noblesse	15	158	1850/2000/2400	3-layer LH-RS	3-layer NH-RS	3-layer NH-RS	ng, uv, ml	sanded, brushed
	15	192	1850/2000/2400	3-layer LH-RS	3-layer NH-RS	3-layer NH-RS	ng, uv, ml	sanded, brushed
	15	240	1850/2000/2400	3-layer LH-RS	-	-	ng, uv, ml	sanded, brushed
elegance	15	158	1850/2000/2400	-	3-layer NH-RS	3-layer NH-RS	ng, uv, ml	sanded, brushed
	15	192	1850/2000/2400	-	3-layer NH-RS	3-layer NH-RS	ng, uv, ml	sanded, brushed
basic	15	158	1850/2000/2400	3-layer LH-RS	3-layer NH-RS	3-layer NH-RS	ng, uv, ml	sanded, brushed
	15	192	1850/2000/2400	3-layer LH-RS	3-layer NH-RS	3-layer NH-RS	ng, uv, ml	sanded, brushed
	15	192	4000/4500/5000	3-layer LH-RS	-	-	natural oil	sanded, brushed
	15	240	1850/2000/2400	3-layer LH-RS	-	-	ng, uv, ml	sanded, brushed
	15	240	4000/4500/5000	3-layer LH-RS	-	-	natural oil	sanded, brushed
	15	280	4000/4500/5000	3-layer LH-RS	-	-	natural oil	sanded, brushed
naturelle	15	158	1850/2000/2400	3-layer LH-RS	-	3-layer NH-RS	ng, uv, ml	sanded, brushed
	15	158	1850/2000/2400	3-layer LH-RS	-	3-layer NH-RS	ng, uv, ml	sanded, brushed

### Technical information

Wood species	Thickness mm	Weight (kg/m <sup>2</sup> )	Moisture content (%)	Lambda	d-Value	Hardness	Fire classification
Oak*	15	8,9 / 8,5	7+/-2 / 7+/-2	0,15 / 0,14	0,100 / 0,107	41 / 41	C <sub>fl</sub> -s1

LH-RS: Hardwood-backing / NH-RS: Softwood-backing

SF-RS: Softwood-veneer-backing, ng: natural oiled / uv: UV oiled / ml: matt lacquer

\* LH-RS / NH-RS \*\* Length 1000 or 1200 mm / Length 1850 or 2000 mm



For more information visit our

website [www.admonter.at](http://www.admonter.at)