


ASH MARRONE

FLOOR



Initial care - with Admonter maintenance oil

You can find more information in the Admonter care- and laying instructions and at www.admonter.eu/en/downloads/



Admonter Natural Floor on under-floor-heating-system

Admonter Natural Floors are ideally suited for under-floor heating systems. We recommend hot-water underfloor heating systems set at low temperature. The surface temperature of 29°C must not be exceeded. Beech is not suitable for under-floor heating systems! We suggest that our products ideally are fully glued down for best results with Admonter elastic adhesive. However, like all engineered boards our planks can be laid as a floating installation (except 2-layer floors and 3-layer floors small (SF-RS), they have to be fully glued down).

More information at www.admonter.at or contact your specialist dealer.

Skirting: Typ2, Typ3 white, Typ4

Grading	Thickn. mm	Width mm	Length mm	Installation and construction			Surface	Texture
				Tongue & groove		lock-it		
rustic	15	154	2000	-	3-layer ^{NH-RS}	-	natural oil	antico
	15	188	2000	-	3-layer ^{NH-RS}	-	natural oil	antico

Technical information

Wood species	Thickness mm	Weight (kg/m ²)	Moisture content (%)	Lambda	d-Value	Hardness	Fire classification
Ash Marrone	15	8,4	5+/-2	0,14	0,107	38	C _s -s1

LH-RS: Hardwood-backing / **NH-RS:** Softwood-backing

SF-RS: Softwood-veneer-backing, **ng:** natural oiled / **uv:** UV oiled / **ml:** matt lacquer

* LH-RS / NH-RS ** Length 1000 or 1200 mm / Length 1850 or 2000 mm



For more information visit our
website **www.admonter.at**

February 2015

A brand of STIA Holzindustrie GmbH, Sägestrasse 539, 8911 Admont, Austria
Errors and changes possible, phone: +43(0)3613/3350-0, fax: +43(0)3613/3350-119, info@admonter.at, www.admonter.at