

# OAK FERRUM



**No final coat of oil required after installation!**

## Admonter Natural Floor on under-floor-heating-system



Admonter Natural Floors are ideally suited for under-floor heating systems. We recommend hot-water underfloor heating systems set at low temperature. The surface temperature of 29°C must not be exceeded. We suggest that our products ideally are fully glued down for best results with Admonter elastic adhesive.

However, like all engineered boards our planks can be laid as a floating installation (except 2-layer floors and 3-layer floors small (SF-RS), they have to be fully glued down). More information at [www.admonter.at](http://www.admonter.at) or contact your specialist dealer.

**Skirting:** Typ2 / Typ3 white / Typ4

Grading	Thickn. mm	Width mm	Length mm	Installation and construction			Surface	Texture
				Tongue & groove		lock-it		
elegance	15	158	1850/2000/2400	-	3-layer <sup>NH-RS</sup>	-	natural oiled	brushed
	15	192	1850/2000/2400	-	3-layer <sup>NH-RS</sup>	-	natural oiled	brushed
basic	15	158	1850/2000/2400	-	3-layer <sup>NH-RS</sup>	-	natural oiled	brushed
	15	192	1850/2000/2400	-	3-layer <sup>NH-RS</sup>	-	natural oiled	brushed
rustic	15	158	1850/2000/2400	-	3-layer <sup>NH-RS</sup>	-	natural oiled	brushed
	15	192	1850/2000/2400	-	3-layer <sup>NH-RS</sup>	-	natural oiled	brushed

**NH-RS - Softwood-backing**

Technical information							
Wood species	Thickn. mm	Weight (kg/m <sup>2</sup> )	Moisture content (%)	Lambda [W/m K]	d-Value R [m <sup>2</sup> K/W]	Hardness [N/mm <sup>2</sup> ]	Fire classification
Oak	15	8,5	7+/-2	0,14	0,107	41	C <sub>fi</sub> -s1*

\* For details concerning reaction to fire and installation conditions, refer to the CE accompanying information on <http://www.admonter.eu/de/downloads/>



For more information visit our website: [www.admonter.at](http://www.admonter.at)